

2017 Light Hot Farm Class

1. ALL GENERAL, SAFETY, AND CHASSIS RULES APPLY
2. Weight class is 6500 lb with a 200 lb moveable differential making it 6700 lb maximum with driver
3. Diesel tractors with turbos can run up to 370 CID
4. N/A tractors can run up to 470 CID at 3800 rpms
5. Turbo diesel tractors are to run a maximum of 3500 rpms (do not exceed)
6. Turbo is a T 04 no billet wheels allowed
7. Drawbars not to exceed 20”
8. All tractors must have stock frame and transmission
9. All drivers are required to wear safety jacket and helmet
10. Tire size is 20.8.34 or 18.4.38
11. No electronically controlled engines of any configuration
12. No intercoolers of any kind are allowed
13. NO ALCOHOL ALLOWED
14. All tractors must have a rops or roll cage
15. Water injection is allowed in the crossover or in front of the charger
16. All tractors must have wide front ends (no narrow fronts)
17. Rotary or A pump allowed, also p pump with 1 plunger per cylinder
18. Fan or harmonic balancer must be shrouded
19. All tractors rpms will be checked by 2 officials
20. All tractors must have a 3 way dump valve for fuel
21. All tractors must have an air shut off
22. NO nitro methane fuel additives of any kind are allowed in diesel or gas tractors
23. All tractors are required to run a safety blanket or steel shield around clutch and bell housing
24. All throttle cable levers must move freely and spring back into shutoff position
25. N/A carburetors must have a 2¹/₄ flange butterfly
26. Must use RPM box
27. Must have seat belts
28. ALL SAFETY EQUIPMENT AND GENERAL RULES WILL BE ENFORCED